


Observabilidad Universal

Cisco Provider Connectivity Assurance

Carles Batalla, Systems Architect Cisco

31 Oct 2025

It's a journey to predictive assurance



CISCO

Service-centric assurance and visibility

Device-centric







You don't know if your customers or your network services are impacted

Service-centric



You'll know if your Layer 2/3
VPN services are OK


If not, you'll know the impact and magnitude—what and where

Combine both

Most tools are ineffective at detecting today's QoE issues

Without deep visibility into micro events:

- 0.53% packet loss leads to a 50% decrease in data throughput
- 5 ms delay leads to a 10% decrease in data throughput
- 10 ms jitter leads to a 10% decrease in data throughput



The quality of the network has a major influence on user quality of experience (QoE)

Reliable data = Efficient outcomes

Accuracy and granularity
















Provider Connectivity Assurance domain



Critical Networks:

- Factories, utilities, transportation
- Public Sector
- Financial institutions
- Connectivity to/from and between DC
- Enterprise to branch offices

Service Providers:

- Mobile/Access to Core
- B2B and wholesale
- Satellite
- Live Events and Broadcast

Solution Components



Provider Connectivity Assurance Platform



• Framework for running centralized services, either fully hosted in the cloud, deployed on customer premise or hybrid.

Assurance Sensors

• Suite of hardware and software sensors, capable of performing layer 2 through layer 4 performance tests

Collectors

- Telemetry Collectors gather data from Cisco devices, Third-Party devices and other network data sources (like SD-WAN).
- Sensor Collectors securely transmit data up to the Assurance Platform.








Sensor Collector




Telemetry Collector



Provider Connectivity Assurance
Sensors

Provider Connectivity Assurance



Visibility: Building the foundation



PCA Assurance Sensors

Assurance Sensor SFP and Modules





- Available as 1Gbps and 10Gbps different variants
- Can be installed:
 - In-line with traffic as any other SFP
 - Or out-of-line in an unused port
- Advantages of Hardware without the inconveniences:
 - No need for extra power of space
 - High precision and accuracy without affecting the measurement
 - L2 and L3 measurements (impossible with




Measuring the real service path: vlan, dscp....

- Service Activation Test (SAT)
 - Remote Full line rate test traffic generation
 - RFC-2544 or Y.1564
- Continuous active performance monitoring standards based:
 - TWAMP (L3), Y.1731 (L2),ICMP Echo (L3)
 - Multi-vendor
 - KPIs beyond the standards: one-way, 50+ KPIs
- Per-flow bandwidth metering (high sample rate)

Service Activation Testing with PCA

- Remote L2 or L3 service testing up to 10Gbps
- Test Reports based on RFC-2544 or Y.1564 standards: Throughput, frame loss, CIR/EIR, etc...
- Exportable (PDF) birth certificate
- Remote and on-demand: reduce truck-rolls





Validate service performance on activation

Standards based Performance Assurance: Extended KPIs

Relevant, actionable, near real-time metrics for SLAs

Comprehensive Set of Metrics per Session

One-way delay, PDV, and IPDV (jitter)

- Min/max/average
- Median (p50)
- Percentile 25/75/95/96/98/99
- Standard deviation

One-way packet statistics

- Packets lost (number and %)
- Loss bursts
- · Longest loss burst
- Shortest loss burst
- Reordered packets (number and %)
- Packets duplicated (number and %)

One-way packet field and QoS metrics

- IP TOS max (DSCP diffserv)
- IP TOS min
- TTL max/min
- VLAN Pbit max/min
- ETH-OAM MEG level max/min
- MOS
- R-value

Service activation testing

Throughput validation – circuit readiness

- RFC2544 generation and reflection
- Y.1564 generation and reflection

Bandwidth metering

Throughput metrics

- Min Throughput Per Flow
- Average Throughput Per Flow
- Max Throughput Per Flow

Time-series data


Telemetry collector:

MDT, gNMI, SNMP, csv, Kafka, etc....



Network-wide service performance visibility

- Deploy in any physical or virtual infrastructure
- Continuous active/synthetic monitoring




Network and service performance visibility Segmented or End-to-End

Insights: Making the data useful



PCA Data Ingestion

- Can ingest any time-series data:
 - From Cisco devices
 - From other time series data sources e.g.: MDT,gNMI, Kafka, SNMP, etc...
- Ingestion pipeline normalizes and enriches data:
 - Common metrics irrespective of vendor
 - Common dashboards, alert profiles, reports and SLAs






Customer portal

A unified view of performance visibility and reporting

- Same user interface look and feel customized data visibility and dashboards
- Have meaningful conversations around planning, service improvements, and SLA management
- One investment to drive mutual benefits the service provider and their internal or end customers







Leveraging metadata

- All Cisco assurance and non-Cisco data can be enriched with metadata
- Metadata is user-defined contextual information
 - Examples: site, region, class of service, geo coordinates, topology, etc.
- How it is used:
 - Filtering, grouping, aggregating relevant data
 - Correlate and find commonalities for root cause analysis and troubleshooting
 - Adds flexibility to dashboards to suit multiple usage scenarios





From the macro view to micro details

Macro view




Analysis




Drill-down and clustering



- Analytics and correlation capabilities
- Metadata enrichment makes data meaningful
- Quickly visualize network and pinpoint problems
- Increase efficacy of operations teams









© 2025 Cisco and/or its affiliates. All rights reserved.

CISCO




Alerts with context




SLAs

Dynamic Thresholds: deviation from baseline



PCA with Cisco Crosswork Automation



ıı|ııı|ıı CISCO